

## SECTION 1: IDENTIFICATION

**Product Name:** TRIPAK ANTI-FRICTION METAL CONDITIONER

**Manufacturer/Supplier:** Tripak Super Lubricants

**Address:** 10811 99 St. Clairmont, AB T8X 5B4

**Phone:** 780-567-4908 **Fax:** 780-567-4277 **Office Email:** admin@tripaksuperlubricants.com

**Emergency Telephone Number:** 780-567-4908

## SECTION 2: HAZARD IDENTIFICATION

<b>Hazard classification:</b>	Flammable Liquids:	Category 4
	Skin Irritation:	Category 3
	Acute Aquatic Toxicity:	Category 1
	Chronic Aquatic Toxicity:	Category 1

**Label elements:**

**Symbols:**



**Signal Word:** WARNING

**Hazard Statements:** Causes mild skin irritation.  
Very toxic to aquatic life with long lasting effects

**Precautionary Statements:**

Wear protective gloves/protective clothing/eye protection/face protection.  
Wash thoroughly after handling.  
Avoid release to the environment.  
Do not eat, drink or smoke while using this product.

---

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

<u>Chemical Names:</u>	<u>% (Vol)</u>	<u>CAS No.</u>
Mineral Spirits	10 - 30	8052-41-3 64742-47-8
Chlorinated paraffin oil	30 - 60	63449-39-8
Petroleum based mineral oil	15 - 40	8012-95-1

## SECTION 4: FIRST-AID MEASURES

**Inhalation:** Unlikely hazard, but if occurs remove to fresh air.

**Ingestion:** Do NOT induce vomiting. Get immediate medical advice/attention. Call a Poison Centre or doctor if victim feels unwell.

**Eye contact:** Flush with water for 15 minutes.

**Skin contact:** Wash with water.

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

**Suitable Extinguishing Media:** Carbon dioxide (CO<sub>2</sub>), BC-powder, Foam, Water mist. Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable Extinguishing Media:** Strong water jet.

**Special Hazards Arising from the Chemical:** Thermal decomposition can lead to the escape of irritating gases and vapors. Avoid breathing dust/fume/gas/mist/vapors/spray. Danger of bursting container in case of fire.

**Hazardous Combustion Products:** Carbon dioxide, carbon monoxide, nitrogen oxides, HCl, un-combusted hydrocarbons, possibly phosgene from chlorinated hydrocarbons.

**Special Protective Equipment and Precautions for Firefighters:** Wear a self-contained breathing apparatus and chemical protective clothing. Use water spray/stream to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**Personal Precautions, Protective Equipment and Emergency Procedures:** Take care that activity is executed only by specialists or authorized personnel. Use personal protective equipment as required. Ventilate affected area.

**Methods and Materials for Containment and Cleaning Up:** Stop leak if safe to do so. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

**Environmental Precautions:** Avoid release to the environment. Collect spillage. Do not allow to enter into ground-water, surface water or drains.

---

## SECTION 7: HANDLING AND STORAGE

---

**Precautions for safe handling:** Avoid contact with eyes, skin and clothing. Keep container tightly closed.

**Conditions for Safe Storage, including any incompatibilities:** Store at temperatures not exceeding 45°C/113°F. Keep only in the original container in a cool, well-ventilated place away from acids. Store in a dry place. Store in a closed container. Avoid release to the environment. Keep away from incompatible materials. Store in accordance with local/regional/national/international regulations.

**Incompatible Materials:** Acids. Strong oxidizing agents

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**Control parameters:** ACGIH TLV and OSHA PEL for Mineral Spirits

TWA: 100 ppm (8 hours)

TWA: 525 mg/m<sup>3</sup> (8 hours)

**Engineering controls:** General ventilation is sufficient.

**Individual protection measures:** Use safety glasses. If usage may result in repeated contact with skin, then gloves and body covering clothing should be used.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES:

---

**Physical state:** Liquid

**Odour and appearance:** Amber liquid, mild sweet odour

**Boiling Point:** Approximately 170°C

**Vapour Pressure:** 0.4 mm Hg @ 20°C

**Vapour Density:** Approximately 5 (air = 1)

**Viscosity:** 17 cSt @ 40°C

**Upper Explosion Limit:** 7%

**Lower Explosion Limit:** 1%

**Solubility in water:** Very low to nil

**%Volatile:** Approximately 20%

**Specific Gravity:** 1.12

**Evaporation Rate:** Not Available

**pH:** Not applicable

**Auto Ignition Temperature:** 245°C

**Flash Point (ASTM D-93):** 80°C

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** No dangerous reaction known under conditions or normal use.

**Chemical stability:** Stable liquid.

**Possibility of hazardous reactions:** Hazardous polymerization will not occur.

**Conditions to avoid:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Elevated temperature.

**Incompatible Materials:** Acids and strong oxidizing agents.

**Hazardous decomposition products:** Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. On combustion, oxides of carbon and nitrogen, hydrogen chloride and possibly phosgene.

## SECTION 11: TOXICOLOGICAL INFORMATION

**Oral LD50:** Rat >2000 mg/kg (Based on data from components)

**Dermal LD50:** Rabbit >2000 mg/kg (Based on data from components)

**LC50:** Rat (inh) 3400 – 8000 (Based on data from components)

**Effects of Acute Overexposure to Product:** Under normal use exposures to vapours or mists are expected to be negligible.

However, breathing high vapour concentrations may cause headaches, nausea, vomiting, dizziness, narcosis, or central nervous system depression. Inhalation of very high vapour concentrations can cause unconsciousness and death. Contact with skin is irritating and can cause erythema and hyperemia. Ingestion can cause diarrhea and vomiting. Any aspiration of mists into lungs, such that may occur from vomiting, may cause chemical pneumonitis and pulmonary edema and hemorrhage possibly resulting in death from chemical pneumonia.

**Effects of Chronic Overexposure to Product:** Under normal use conditions exposures are expected to be negligible. However, prolonged or repeated skin contact at low levels can cause irritation, dermatitis, and may aggravate pre-existing dermatitis. Prolonged or repeated exposure to high vapour concentrations may cause neural dysfunction. Effects on the kidney, liver, and heart have been reported caused by volatile chlorinated paraffins from chronic exposure, but the effect is expected to be much less for chlorinated paraffin oil, particularly due to a lower volatility and potential of exposure to vapour. Studies have shown that many petroleum hydrocarbons pose potential health risks to humans so exposure should be minimized.

**Irritancy:** Mild skin irritant. Inhalation of vapours can irritate respiratory tract and lungs.

**Sensitization to Product:** In rare cases cardiac sensitization in individuals from exposure to high concentrations of hydrocarbon vapours can occur, resulting in cardiac arrhythmia.

**Carcinogenicity:** None of the components in the raw materials have been reported to be carcinogens.

**Teratogenicity and Reproductive Toxicity:** This product contains a small amount of xylene, which has been known to cause some reproductive toxicity.

**Synergistic Effects:** No evidence.

**Mutagenicity:** No evidence.

## SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity (Chloroalkanes):** LC50, Rainbow trout, Donaldson trout (*Oncorhynchus mykiss*) >0.1 mg/l, 96 hours

**Aquatic toxicity:** Very toxic to aquatic organisms. May cause long lasting harmful effects to aquatic life.  
Avoid contaminating waterways.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Disposal Methods:** Containers should be cleaned and recycled. Spilled or contaminated product should be collected and disposed in accordance with local regulations.

## SECTION 14: TRANSPORT INFORMATION

**TDG information:**

SHIPPING NAME: Flammable Liquids NOS, PIN: UN1993, CLASS: 3, PACKING GROUP: III

Special Provision: In containers of 450 L or less, this product is not classified as Dangerous Goods according to TDG exemption 1.33

---

## SECTION 15: REGULATORY INFORMATION

---

**WHMIS 2015 regulations:**

<b>Hazard classification:</b>	Flammable Liquids:	Category 4
	Skin Irritation:	Category 3
	Acute Aquatic Toxicity:	Category 1
	Chronic Aquatic Toxicity:	Category 1

---

## SECTION 16: OTHER INFORMATION

---

**Preparation date:** May 25, 2017

**Prepared by:** D. Cameron

The information contained in this SAFETY DATA SHEET (the "Information") relates to the specific material designated and may not be valid for such material when used in combination with any other materials or in any process. The information is provided solely for the purpose of compliance with government legislation in force from time to time relating to the sale or distribution of materials of the same type as the specific material designated. Other than to the extent necessarily mandated by such legislation, no representation, warranty or guarantee is made as to the accuracy, reliability or completeness of the Information. The provision and publication of the Information is no way intended to be relied upon by any persons, including, without limitation, users of the materials to which this SAFETY DATA SHEET applies, for any whatsoever, and is not in any circumstances to be the basis for or acceptance of liability for loss or damage of any kind whatsoever that may occur from the use or publication of, or reliance upon the Information. It is the user's responsibility to satisfy himself as to suitability and the completeness of the Information for his own particular use and the particular circumstances of such use. Any emergency, first aid, spillage control or other procedure should only be attempted by qualified personnel.